

## ExxonMobil 150 Exxon Sawguide Oil

Category : Fluid , Lubricant

**Material Notes:**

EXXON SAWGUIDE OIL is specifically formulated to lubricate the thin saw blades of modern gang saws and edgers. The choice of viscosity grade depends on equipment type, lubricant delivery system design and ambient temperatures. Your Exxon representative can assist in selecting the proper viscosity grade. EXXON SAWGUIDE OIL is specially formulated to meet the lubrication requirements of modern gang saws and edgers.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ExxonMobil-150-Exxon-Sawguide-Oil.php](http://www.lookpolymers.com/polymer_ExxonMobil-150-Exxon-Sawguide-Oil.php)

| Physical Properties                  | Metric               | English                   | Comments   |
|--------------------------------------|----------------------|---------------------------|------------|
| Density                              | 0.889 g/cc           | 0.0321 lb/in <sup>3</sup> |            |
|                                      | @Temperature 15.0 °C | @Temperature 59.0 °F      |            |
| Kinematic Viscosity at 40°C (104°F)  | 150 cSt              | 150 cSt                   |            |
| Kinematic Viscosity at 100°C (212°F) | 16.4 cSt             | 16.4 cSt                  |            |
| ASTM Color                           | 2.5                  | 2.5                       | ASTM D1500 |

| Mechanical Properties | Metric   | English      | Comments                    |
|-----------------------|----------|--------------|-----------------------------|
| Falex Load Test       | 0.0110 g | 0.0000243 lb | Low Load, 600 lb for 2.5 hr |

| Thermal Properties | Metric   | English | Comments |
|--------------------|----------|---------|----------|
| Pour Point         | -12.0 °C | 10.4 °F |          |
| Flash Point        | 222 °C   | 432 °F  |          |

| Component Elements Properties | Metric   | English  | Comments |
|-------------------------------|----------|----------|----------|
| H2O                           | 0.0037 % | 0.0037 % |          |

| Descriptive Properties               | Value | Comments   |
|--------------------------------------|-------|------------|
| Rust Prevention, Distilled Water     | pass  | ASTM D665A |
| Rust Prevention, Synthetic Sea Water | pass  | ASTM D665B |

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

**Tel : +86 021-51131842**

**Mobile : +86 13061808058**

**Skype : lookpolymers**

**Address : United North Road 215, Fengxian District, Shanghai City, China**