

ExxonMobil ESCOREZ™ 1102 (Americas) Petroleum Hydrocarbon Resin

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer , Adhesive

Material Notes:

Aliphatic hydrocarbon resin which is designed for use in a variety of applications. Availability: Central America, North America and South America. Information provided by ExxonMobil Chemical

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-ESCOREZ-1102-Americas-Petroleum-Hydrocarbon-Resin.php

Physical Properties	Metric	English	Comments
Viscosity	1650 cP	1650 cP	ETM 22-31
	@Temperature 160 °C	@Temperature 320 °F	
Molecular Weight	1300 g/mol	1300 g/mol	Mn; ETM 300-83
	2900 g/mol	2900 g/mol	Mw; ETM 300-83

Thermal Properties	Metric	English	Comments
Softening Point	100 °C	212 °F	ETM 22-4
Glass Transition Temp, Tg	50.0 °C	122 °F	ETM 300-90

Descriptive Properties	Value	Comments
Color-Initial	3.0 G	ETM 22-13
Thermal Color Stability	12.0 G	5 hr, 175°C, ETM 22-14
Wax Cloud Point	110°C	ETM 22-10

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China