

ExxonMobil Escor™ 5200 Ethylene Acrylic Acid Copolymer Resin

Category: Polymer, Thermoplastic, Ethylene Acrylic Acid

Material Notes:

Product Description: Escor 5200 is an ethylene acrylic acid copolymer with a high comonomer content. Escore 5200 can be used pure or as a component in blend formulations for bonding applications where applications where medium viscosity and very good adhesion to polar materials (metals, nylon, glass, ...) are key requirements. Availability: Africa & Middle East, Asia Pacific and Europe Additive: Antiblock:

NoSlip: No Thermal Stabilizer: NoApplications: Adhesive Applications Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Escor-5200-Ethylene-Acrylic-Acid-Copolymer-Resin.php

| Physical Properties | Metric | English | Comments |
|----------------------|-------------|---------------|-------------------|
| Density | 0.944 g/cc | 0.0341 lb/in³ | ExxonMobil method |
| Acrylic Acid Content | 15 % | 15 % | ExxonMobil Method |
| Melt Flow | 38 g/10 min | 38 g/10 min | ASTM D1238 |

| Thermal Properties | Metric | English | Comments |
|-----------------------|-----------|-----------|---------------------------------------|
| Melting Point | <= 190 °C | <= 374 °F | Peak Melting Point; ExxonMobil method |
| Vicat Softening Point | 57.2 °C | 135 °F | ASTM D1525 |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China