

ExxonMobil Escorene™ UL 12530CC Ethylene Vinyl Acetate Copolymer (European Grade)

Category : Polymer , Thermoplastic , Ethylene Vinyl Acetate

Material Notes:

Product Description: UL 12530CC is a copolymer of ethylene and vinyl acetate. Availability: Africa & Middle East and Europe Additive:

Antiblock: NoSlip: No Thermal Stabilizer: Yes Applications: Hot Melt Adhesives Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Escorene-UL-12530CC-Ethylene-Vinyl-Acetate-Copolymer-European-Grade.php

Physical Properties	Metric	English	Comments
Density	0.951 g/cc	0.0344 lb/in³	ExxonMobil method
Vinyl Acetate Content	30 %	30 %	ExxonMobil method
Melt Flow	130 g/10 min	130 g/10 min	ASTM D1238

Thermal Properties	Metric	English	Comments
Melting Point	<= 144 °C	<= 291 °F	Peak Melting Point; ExxonMobil method

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China