

ExxonMobil Escorene™ UL 15019CC Ethylene Vinyl Acetate Copolymer (European Grade)

Category : Polymer , Thermoplastic , Ethylene Vinyl Acetate

Material Notes:

Product Description: UL 15019CC is a copolymer of ethylene and vinyl acetate. Availability: Africa & Middle East and Europe Additive:

Antiblock: NoSlip: No Thermal Stabilizer: Yes Applications: Hot Melt Adhesives Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Escorene-UL-15019CC-Ethylene-Vinyl-Acetate-Copolymer-European-Grade.php

Physical Properties	Metric	English	Comments
Density	0.939 g/cc	0.0339 lb/in ³	ExxonMobil method
Vinyl Acetate Content	19 %	19 %	ExxonMobil method
Melt Flow	150 g/10 min	150 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	88	88	Molded Properties; ASTM D2240
Tensile Strength at Break	4.90 MPa	710 psi	(20 in/min), Molded Properties; ASTM D638
Elongation at Break	650 %	650 %	(20 in/min), Molded Properties; ASTM D638
Tensile Modulus	0.0338 GPa	4.90 ksi	(0.2 in/min), Molded Properties; ASTM D638

Thermal Properties	Metric	English	Comments
Melting Point	<= 181 °C	<= 358 °F	Peak Melting Point; ExxonMobil method

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China