

ExxonMobil Escorene™ UL 53019CC Ethylene Vinyl Acetate Copolymer (European Grade)

Category : Polymer , Thermoplastic , Ethylene Vinyl Acetate

Material Notes:

Product Description: UL 53019CC is a copolymer of ethylene and vinyl acetate. Availability: Africa & Middle East and Europe Additive:

Antiblock: NoSlip: No Thermal Stabilizer: Yes Free Flowing Agent: No Applications: Hot Melt Adhesives Information provided by

ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Escorene-UL-53019CC-Ethylene-Vinyl-Acetate-Copolymer-European-Grade.php

Physical Properties	Metric	English	Comments
Density	0.937 g/cc	0.0339 lb/in ³	ExxonMobil method
Vinyl Acetate Content	19 %	19 %	ExxonMobil method
Melt Flow	530 g/10 min	530 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	86	86	Molded Properties; ASTM D2240
Tensile Strength at Break	3.17 MPa	460 psi	(20 in/min), Molded Properties; ASTM D638
Elongation at Break	230 %	230 %	(20 in/min), Molded Properties; ASTM D638
Tensile Modulus	0.0269 GPa	3.90 ksi	(0.2 in/min), Molded Properties; ASTM D638

Thermal Properties	Metric	English	Comments
Melting Point	<= 176 °C	<= 349 °F	Peak Melting Point; ExxonMobil method

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China