

ExxonMobil Escorene® UL 7620 Adhesive Application Resin (discontinued **)

Category : Polymer , Adhesive , Thermoplastic , Ethylene Vinyl Acetate , Ethylene Vinyl Acetate Copolymer (EVA), Adhesive/Sealant Grade

Material Notes:

Escorene Ultra UL 7620 is a medium flow rate, 24% vinyl acetate copolymer that has very good compatibility with hydrocarbon tackifiers and most waxes. It is suitable for making hot melt adhesives, sealants and wax blends. Information provided by ExxonMobil Chemical

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Escorene-UL-7620-Adhesive-Application-Resin-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.941 g/cc	0.0340 lb/in ³	ExxonMobil Method
Vinyl Acetate Content	24 %	24 %	ExxonMobil Method
Melt Flow	112 g/10 min	112 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	71	71	15s; ASTM D2240
Hardness, Shore D	23	23	15s; ASTM D2240
Tensile Strength at Break	3.52 MPa	510 psi	ASTM D638
Elongation at Break	700 %	700 %	ASTM D638
Flexural Modulus	0.0314 GPa	4.55 ksi	1% secant; ASTM D790

Thermal Properties	Metric	English	Comments
Melting Point	73.3 °C	164 °F	Peak Melting Temperature; ExxonMobil Method
Vicat Softening Point	41.1 °C	106 °F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China