

ExxonMobil Exxsol™ D220/230 Dearomatized Fluid

Category : Fluid

Material Notes:

Availability: Africa & Middle East and Europe Appearance: Clear/Transparent Liquid Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Exxsol-D220230-Deaeromatized-Fluid.php

Physical Properties	Metric	English	Comments
Density	0.809 g/cc	0.0292 lb/in ³	ASTM D4052
	@Temperature 15.0 °C	@Temperature 59.0 °F	
Kinematic Viscosity	2.44 cSt	2.44 cSt	ASTM D445
Vapor Pressure	0.00107 bar	0.800 torr	ExxonMobil Method
	@Temperature 20.0 °C	@Temperature 68.0 °F	

Thermal Properties	Metric	English	Comments
Boiling Point	219 °C	426 °F	Initial; ASTM 1078
	234 °C	453 °F	Final; ASTM 1078
Flash Point	91.1 °C	196 °F	Method A; ASTM D93

Descriptive Properties	Value	Comments
Aniline Point	167°F	Method E, ASTM D611
Aromatic Content	0.002	UV, ExxonMobil Method

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China