

ExxonMobil Exxsol™ DSP60/95 S Dearomatized Fluid

Category : Fluid

Material Notes:

Availability: Africa & Middle East and Europe Appearance: Clear/Transparent Liquid Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Exxsol-DSP6095-S-Deaeromatized-Fluid.php

Physical Properties	Metric	English	Comments
Density	0.699 g/cc	0.0252 lb/in ³	ISO 12185
	@Temperature 15.0 °C	@Temperature 59.0 °F	
Kinematic Viscosity	0.54 cSt	0.54 cSt	ASTM D445
Vapor Pressure	0.107 bar	80.0 torr	ExxonMobil Method
	@Temperature 20.0 °C	@Temperature 68.0 °F	

Thermal Properties	Metric	English	Comments
Boiling Point	67.2 °C	153 °F	Initial; ASTM 1078
Flash Point	<= 0.000 °C	<= 32.0 °F	ASTM D56

Descriptive Properties	Value	Comments
Aniline Point	144°F	Method E, ASTM D611
Aromatic Content	<10 wt ppm	UV, ExxonMobil Method
Dry Point	208°F	ASTM 1078

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China