

ExxonMobil Isopar™ E Isoparaffin Fluid

Category : Fluid

Material Notes:

Product Description: A clear isoparaffin fluid, typically containing less than 1 ppm benzene and less than 1 ppm sulfur. Appearance:

Clear/Transparent Liquid Availability: Africa & Middle East, Asia Pacific, Europe, Central America, North America and South

America Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Isopar-E-Isoparaffin-Fluid.php

Physical Properties	Metric	English	Comments
Density	0.723 g/cc	0.0261 lb/in ³	ASTM D4052
	@Temperature 15.6 °C	@Temperature 60.0 °F	
Kinematic Viscosity	0.83 cSt	0.83 cSt	ASTM D445
Vapor Pressure	0.0133 bar	10.0 torr	ExxonMobil Method
	@Temperature 20.0 °C	@Temperature 68.0 °F	

Thermal Properties	Metric	English	Comments
Boiling Point	114 °C	237 °F	Initial; ASTM D86
Flash Point	7.22 °C	45.0 °F	ASTM D56

Descriptive Properties	Value	Comments
Aniline Point	162°F	Method E, ASTM D611
Aromatic Content	10 wt ppm	ExxonMobil Method
Dry Point	282°F	ASTM D86

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China