

ExxonMobil Isopar™ G (AM) Isoparaffin Fluid

Category : Fluid

Material Notes:

Product Description: A clear isoparaffin fluid, typically containing less than 1 ppm benzene and less than 1 ppm sulfur. Appearance:

Clear/Transparent Liquid Availability: Asia Pacific, Central America, North America and South America Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Isopar-G-AM-Isoparaffin-Fluid.php

Physical Properties	Metric	English	Comments
Density	0.749 g/cc @Temperature 15.6 °C	0.0271 lb/in³ @Temperature 60.0 °F	ASTM D4052
Kinematic Viscosity	1.49 cSt	1.49 cSt	ASTM D445
Vapor Pressure	0.00133 bar @Temperature 20.0 °C	1.00 torr @Temperature 68.0 °F	ExxonMobil Method

Thermal Properties	Metric	English	Comments
Boiling Point	166 °C	331 °F	Initial; ASTM D86
Flash Point	43.9 °C	111 °F	ASTM D56

Descriptive Properties	Value	Comments
Aniline Point	183°F	Method E, ASTM D611
Aromatic Content	10 wt ppm	ExxonMobil Method
Dry Point	351°F	ASTM D86

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China