

ExxonMobil Isopar™ M (AM) Isoparaffin Fluid

Category : Fluid

Material Notes:

Product Description: A clear isoparaffin fluid, typically containing less than 1 ppm benzene and less than 1 ppm sulfur. Appearance:

Clear/Transparent Liquid Availability: Asia Pacific, Central America, South America and North America Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Isopar-M-AM-Isoparaffin-Fluid.php

Physical Properties	Metric	English	Comments
Density	0.786 g/cc @Temperature 15.6 °C	0.0284 lb/in³ @Temperature 60.0 °F	ASTM D4052
Kinematic Viscosity	4.23 cSt	4.23 cSt	ASTM D445
Vapor Pressure	<= 0.000133 bar @Temperature 20.0 °C	<= 0.100 torr @Temperature 68.0 °F	ExxonMobil Method

Thermal Properties	Metric	English	Comments
Boiling Point	225 °C	437 °F	Initial; ASTM D86
Flash Point	95.0 °C	203 °F	Method A; ASTM D93

Descriptive Properties	Value	Comments
Aniline Point	199°F	Method E, ASTM D611
Aromatic Content	40 wt ppm	UV, ExxonMobil Method
Dry Point	489°F	ASTM D86

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China