

ExxonMobil Mobil 1 5W-30

Category: Fluid, Lubricant

Material Notes:

Mobil 1 5W-30 is a high performance fully synthetic engine oil designed to exceed the industry's toughest standards and outperform all conventional oils.. Mobil 1 5W-30 is engineered to help keep engines running like new and extend engine life. Mobil 1 technology has been selected as original equipment by car builders such as, Chevrolet Corvette, Cadillac, Mercedes Benz AMG, Porsche, Dodge Viper, and Dodge Ram SRT 10.

Order this product through the following link: http://www.lookpolymers.com/polymer_ExxonMobil-Mobil-1-5W-30.php

Physical Properties	Metric	English	Comments
Density	0.800 g/cc	0.0289 lb/in³	ASTM D4052
	@Temperature 15.0 °C	@Temperature 59.0 °F	
Viscosity	3.09 cP	3.09 cP	High Temperature High Shear (HTHS); ASTM D4683
	@Temperature 150 °C	@Temperature 302 °F	
Viscosity Measurement	169	169	Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	64.8 cSt	64.8 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	11.3 cSt	11.3 cSt	ASTM D445
Ash	1.0 %	1.0 %	Sulfated Ash, wt%; ASTM D874

Thermal Properties	Metric	English	Comments
Pour Point	-54.0 °C	-65.2 °F	ASTM D97
Flash Point	230 °C	446 °F	ASTM D92

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China