

ExxonMobil PP2252E1 Homopolymer

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene, Extrusion Grade

Material Notes:

Product Description: Medium melt flow rate homopolymer designed for high speed extrusion of woven fabrics exhibiting low water carry over. Availability: North America Features: Balanced Stiffness/Toughness General Purpose Low Water Carryover Uses: Carpet Backing Compounding Fabrics Fibers Packaging Processing Method: Extrusion Information provided by ExxonMobil Chemical

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-PP2252E1-Homopolymer.php

Physical Properties	Metric	English	Comments
Density	0.900 g/cc	0.0325 lb/in ³	ASTM D792
Melt Flow	3.5 g/10 min @Load 2.16 kg, Temperature 230 °C	3.5 g/10 min @Load 4.76 lb, Temperature 446 °F	ASTM D1238

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China