

## **ExxonMobil Paxon™ EX49-006 Extrusion Grade Resin (discontinued \*\*)**

Category: Polymer, Thermoplastic, Polyethylene (PE), HDPE, High Density Polyethylene (HDPE), Extruded

## **Material Notes:**

EX49-006 is an unstabilized high density polyethylene extrusion grade polyethylene copolymer. It is designed for blending and compounding with fillers, such as wood flour, to give uniform mixing and dispersion. Information provided by ExxonMobil Chemical

Order this product through the following link:

http://www.lookpolymers.com/polymer\_ExxonMobil-Paxon-EX49-006-Extrusion-Grade-Resin-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments	
Density	0.950 g/cc	0.0343 lb/in <sup>3</sup>	ASTM D4883	
Melt Flow	0.43 g/10 min	0.43 g/10 min		
	@Load 2.16 kg, Temperature 190 °C	@Load 4.76 lb, Temperature 374 °F	ASTM D1238	

Descriptive Properties	Value	Comments
Features	Thermal Stabilizer	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China