

ExxonMobil Vistalon™ 3666 Ethylene-Propylene Terpolymer (EPDM)

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE)

Material Notes:

Vistalon 3666 EPDM rubber is an oil extended grade of very high molecular weight, medium ethylene level and medium diene content. It is used to produce low hardness articles, appliance gaskets, shock absorbers, resilient profiles and hoses with excellent compression set. This grade can be used in blends with other Vistalon EPDM grades to enhance elastic properties. Key Features: High elasticity and good low temperature properties. Excellent collapse resistance to compounds. High oil loadability. Availability: Africa & Middle East, Europe, North America, Asia Pacific, Latin America and South America. Information provided by ExxonMobil Chemical

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Vistalon-3666-Ethylene-Propylene-Terpolymer-EPDM.php

Physical Properties	Metric	English	Comments
Mooney Viscosity	52 @Temperature 125 °C	52 @Temperature 257 °F	ML 1 + 4; ASTM D1646

Descriptive Properties	Value	Comments
ENB Content	4.5%	ASTM D6047
Ethylene Content	64%	ASTM D3900
Oil Content	75phr	ExxonMobil Method

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China