

Fainplast Compounds PH 50/AM-UV Flexible PVC, Transparent Extrusion

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Transparent

Material Notes:

Gaskets anti mould and anti-UV

Order this product through the following link:

http://www.lookpolymers.com/polymer_Fainplast-Compounds-PH-50AM-UV-Flexible-PVC-Transparent-Extrusion.php

Physical Properties	Metric	English	Comments
Density	1.14 - 1.18 g/cc	0.0412 - 0.0426 lb/in ³	ISO R 1183

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	48 - 52	48 - 52	ISO R 868
Tensile Strength at Break	8.00 MPa	1160 psi	ISO R 527
Elongation at Break	400 %	400 %	ISO R 527

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-50.0 °C	-58.0 °F	Cold Flex; ISO 458/2

Optical Properties	Metric	English	Comments
Transmission, Visible	90 %	90 %	transparent; thickness not quantified

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China