

Garlock 19 SBR Rubber Gasketing, Cotton Reinforced

Category: Polymer, Thermoset, Rubber or Thermoset Elastomer (TSE), Styrene Butadiene Rubber

Material Notes:

SBR rubber with cotton sheeting as fabric insertCombines elasticity and extensibility of rubber with strength of fabric insert. Specially compounded in varying burst strengths for almost any service conditionInformation provided by Garlock Rubber Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_Garlock-19-SBR-Rubber-Gasketing-Cotton-Reinforced.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	75 - 85	75 - 85	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	93.3 °C	200 °F	
	@Pressure 1.72 MPa	@Pressure 250 psi	

Electrical Properties	Metric	English	Comments
Dielectric Strength	1.22 kV/mm	31.0 kV/in	Unconditioned; ASTM D149
	@Thickness 3.17 mm	@Thickness 0.125 in	

Descriptive Properties	Value	Comments
Color	Black	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China