

Garlock 9200 Nitrile Rubber Gasketing, Nylon Insert

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE)

Material Notes:

Nitrile rubber with proprietary nylon insert Combines elasticity and extensibility of rubber with strength of fabric insert. Specially compounded in varying burst strengths for almost any service condition. Information provided by Garlock Rubber Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_Garlock-9200-Nitrile-Rubber-Gasketing-Nylon-Insert.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	65 - 75	65 - 75	
Tensile Strength	13.8 MPa	2000 psi	ASTM D412
Elongation at Break	>= 250 %	>= 250 %	ASTM D412

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	121 Â°C @Pressure 1.72 MPa	250 Â°F @Pressure 250 psi	

Electrical Properties	Metric	English	Comments
Dielectric Strength	0.315 kV/mm @Thickness 3.17 mm	8.00 kV/in @Thickness 0.125 in	Unconditioned; ASTM D149

Descriptive Properties	Value	Comments
Color	Black	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China