

## Garlock Super Rinohideâ, ¢ 7160 SBR Rubber Lining

Category: Polymer, Thermoset, Rubber or Thermoset Elastomer (TSE), Styrene Butadiene Rubber

## **Material Notes:**

SBR rubber lining for protection applications such as chute lining and skirtboards. Super RINOHIDEâ,¢, in particular, performs with superior resistance to abrasion, impact, aging and weathering. It is made of specially compounded SBR to withstand severe impact and abrasion. Information provided by Garlock Rubber Technologies

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Garlock-Super-Rinohide-7160-SBR-Rubber-Lining.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	55 - 65	55 - 65	
Tensile Strength	>= 17.2 MPa	>= 2500 psi	
	19.3 MPa	2800 psi	ТурісаІ
Elongation at Break	>= 500 %	>= 500 %	

Thermal Properties	Metric	English	Comments	
Maximum Service Temperature, Air	93.3 °C	200 °F		
Minimum Service Temperature, Air	-28.9 °C	-20.0 °F		

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China