

Gouda Vuurvast ADHESIET 150 Dry Air-Setting Refractory Mortar

Category : Ceramic , Oxide , Aluminum Oxide , Silicon Oxide

Material Notes:

Description: Adhesiet 150 is an air setting mortar with a sodium silicate bond and is supplied as a dry powder. Because of the special mix of the raw materials it can be used up to 1500Â°C. Remarks: Adhesiet mortars can be stored for an unlimited time if kept dry and cool. Only clean water should be added to make the mortar ready for use. Information provided by Gouda Vuurvast.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Gouda-Vuurvast-ADHESIET-150-Dry-Air-Setting-Refractory-Mortar.php

Physical Properties	Metric	English	Comments
Particle Size	<= 500 Âµm	<= 500 Âµm	Grain Size

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	1500 Â°C	2730 Â°F	

Component Elements Properties	Metric	English	Comments
Al2O3	60 %	60 %	
Fe2O3	1.5 %	1.5 %	
Na2O or K2O	2.0 %	2.0 %	
SiO2	33 %	33 %	

Descriptive Properties	Value	Comments
Base Material	chamotte/bauxite	
Mixing Water	22-27 liters	per 100 kgs dry material

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China