

Gwent Electronic Materials C2030217D2 Aluminium for PTC paste

Category : Fluid , Metal , Other Engineering Material , Ceramic/Metallic Coating

Material Notes:

Aluminium Ink designed to give good ohmic contact on to barium titanate PTC components. This product is particularly good where large volumes of PTC components are being processed in belt furnaces conditions, where improved stain resistance and good visual appearance are required. Screen Printing Equipment: semi-automatic, manual Screen Types: stainless steel, polyester Substrate: PTC ceramic parts Information provided by Gwent Electronic Materials Ltd.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Gwent-Electronic-Materials-C2030217D2-Aluminium-for-PTC-paste.php

Physical Properties	Metric	English	Comments
Solids Content	67 - 72 %	67 - 72 %	
	@Temperature 150 Â°C	@Temperature 302 Â°F	
Viscosity	10500 - 14000 cP	10500 - 14000 cP	
	@Shear Rate 230 1/s, Temperature 25.0 Â°C	@Shear Rate 230 1/s, Temperature 77.0 Â°F	Haake VT 550 PK1.1Â°
Storage Temperature	20.0 Â°C	68.0 Â°F	sealed container

Processing Properties	Metric	English	Comments
Sintering Temperature	780 - 910 Â°C	1440 - 1670 Â°F	
Cure Time	15.0 min	0.250 hour	
	@Temperature 150 Â°C	@Temperature 302 Â°F	
Shelf Life	6.00 Month	6.00 Month	

Descriptive Properties	Value	Comments
Coverage cm2/g	227	Using a 230 mesh stainless steel screen

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China