

## Haysite 24500 Vinyl Ester BMC, 20% Glass Reinforced

Category: Polymer, Thermoset, Filled/Reinforced Thermoset, Polyester, TS, Thermoset Polyester Glass Filled BMC, Vinyl Ester

## **Material Notes:**

The 24500 series bulk molding compound offers good mechanical performance and excellent resistance to corrosive agents. This grade is formulated with a vinyl ester resin system and can be compression, transfer, or injection molded.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Haysite-24500-Vinyl-Ester-BMC-20-Glass-Reinforced.php

Physical Properties	Metric	English	Comments
Density	1.77 g/cc	0.0639 lb/in³	ASTM D572
Water Absorption	0.29 %	0.29 %	ASTM D570

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	48.0 MPa	6960 psi	
Flexural Strength	159 MPa	23100 psi	
Compressive Strength	145 MPa	21000 psi	
Izod Impact, Notched	5.90 J/cm	11.1 ft-lb/in	edgewise; ASTM D256

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	130 °C	266 °F	temperature rating

Electrical Properties	Metric	English	Comments
Dielectric Strength	15.0 kV/mm	381 kV/in	Perpendicular (ASTM D149), Short Time
Arc Resistance	187 sec	187 sec	ASTM D495

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China