

Henkel Hysol MA 562 Core Splice Adhesive

Category : Polymer , Adhesive , Film , Thermoset , Epoxy , Epoxy Adhesive

Material Notes:

General-purpose 250°F / 121°C or 350°F / 177°C curing foaming adhesive. Designed for service temperatures from -67°F / -55°C to 350°F / 177°C. Medium tack, nonmetallic, low exotherm properties, excellent slump resistance, uniform expansion, qualified to many industry specifications.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Henkel-Hysol-MA-562-Core-Splice-Adhesive.php

Physical Properties	Metric	English	Comments
Storage Temperature	-18.0 °C	-0.400 °F	

Mechanical Properties	Metric	English	Comments
Adhesive Bond Strength	8.00 MPa	1160 psi	tube shears
	@Temperature 121 °C	@Temperature 250 °F	
	8.30 MPa	1200 psi	tube shears
	@Temperature 25.0 °C	@Temperature 77.0 °F	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	177 °C	351 °F	

Processing Properties	Metric	English	Comments
Cure Time	60.0 min	1.00 hour	
	@Temperature 177 °C	@Temperature 351 °F	
	90.0 min	1.50 hour	
	@Temperature 121 °C	@Temperature 250 °F	

Descriptive Properties	Value	Comments
Out-Time (days)	10	at 32°C
	20	at 25°C

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China