

Henkel Hysol MA 562SFR Core Splice Adhesive

Category : Polymer , Adhesive , Film , Thermoset , Epoxy , Epoxy Adhesive

Material Notes:

Modified epoxy foaming adhesive that may be cured at 250°F / 121°C or 350°F / 177°C. Flame-retardant, nonmetallic, medium tack, excellent slump resistance.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Henkel-Hysol-MA-562SFR-Core-Splice-Adhesive.php

Mechanical Properties	Metric	English	Comments
Adhesive Bond Strength	5.80 MPa	841 psi	tube shears
	@Temperature 25.0 °C	@Temperature 77.0 °F	
	6.90 MPa	1000 psi	tube shears
	@Temperature 121 °C	@Temperature 250 °F	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	177 °C	351 °F	

Processing Properties	Metric	English	Comments
Cure Time	60.0 min	1.00 hour	
	@Temperature 177 °C	@Temperature 351 °F	
	90.0 min	1.50 hour	
	@Temperature 121 °C	@Temperature 250 °F	

Descriptive Properties	Value	Comments
Out-Time (days)	10	at 25°C
	10	at 32°C

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China