

Hexcel® Redux® 609 (0.04 psf) Adhesive film for bonding metallic and composite components

Category : Polymer , Adhesive , Film , Thermoset , Epoxy , Epoxy Adhesive

Material Notes:

Redux 609 is a 250°F curing modified epoxy film adhesive containing a cotton scrim for easy handling and glue-line thickness control. It is available at standard areal weights of 0.06 psf and 0.04 psf and is also available unsupported at 0.06 psf. Features: Flexible cure cycle; Good lap shear performance at temperatures ranging from -67°F to 180°F; Good peel properties from -67°F to 180°F; Good tack to assist in adhesive joint assembly; Less than 1% volatile content; Suitable for bonding a wide range of substrates. Applications: Aluminum to aluminum bonding; Sandwich bonding with a variety of skins and cores

Order this product through the following link:

http://www.lookpolymers.com/polymer_Hexcel-Redux-609-004-psf-Adhesive-film-for-bonding-metallic-and-composite-components.php

Physical Properties	Metric	English	Comments
Storage Temperature	-17.8 °C	0.000 °F	

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	4.48 MPa	650 psi	Flatwise Tensile
Shear Strength	31.0 MPa	4500 psi	Lap Shear
	@Temperature 21.1 °C	@Temperature 70.0 °F	
	31.0 MPa	4500 psi	Lap Shear
	@Temperature 48.9 °C	@Temperature 120 °F	

Processing Properties	Metric	English	Comments
Shelf Life	12.0 Month	12.0 Month	
	@Temperature -17.8 °C	@Temperature 0.000 °F	

Descriptive Properties	Value	Comments
Areal Weight (psf)	0.04	
Roll Width (in)	49	
Standard Roll (ft2)	1075	
Support	Cotton Scrim	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China