

Huntsman AVALON® 80 AE Thermoplastic Polyurethane

Category : Polymer , Thermoplastic , Polyurethane, TP , Thermoplastic Polyurethane (TPUR), Polyester Grade

Material Notes:

Performance Features: AVALON® injection molding products are trusted worldwide to deliver: Outstanding flex performance Excellent slip resistance Perfect surface definition Transparency and translucency Oil resistance Fast cycle times Outstanding abrasion and scratch resistance Perfect color match with master batches Rubber-like look and feel Excellent bonding. Information provided by Alliance Polymers

Order this product through the following link:

http://www.lookpolymers.com/polymer_Huntsman-AVALON-80-AE-Thermoplastic-Polyurethane.php

Physical Properties	Metric	English	Comments
Density	1.22 g/cc	0.0441 lb/in ³	ISO 2781

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	80	80	ISO 868
Hardness, Shore D	30	30	ISO 868
Tensile Strength at Break	26.0 MPa	3770 psi	ISO 37
Elongation at Break	600 %	600 %	ISO 37
100% Modulus	0.00500 GPa	0.725 ksi	ISO 37
300% Modulus	0.00800 GPa	1.16 ksi	ISO 37
Tear Strength	80.0 kN/m	456 pli	ISO 34B
Abrasion	35	35	mm ³ ; ISO 4649

Descriptive Properties	Value	Comments
Ross Flex	-10°C, BS 5131	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China