

ICO Polymers ICOFLO 510-5053 500 Micron LDPE Powder

Category : Polymer , Thermoplastic , Polyethylene (PE) , LDPE , Low Density Polyethylene (LDPE), Masterbatch Grade

Material Notes:

Description: ICOFLO 510-5053 is a premium polyethylene powder specifically designed to be used in the preparation of masterbatch (concentrate). By utilizing a free flowing powder as a carrier in masterbatch (instead of pellet), superior color development or additive dispersion can be achieved in the final concentrate. Key Characteristics: good stiffness, good impact strength and excellent appearance.

Information provided by ICO Polymers. A Schulman acquired ICO, Inc. in 2010.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ICO-Polymers-ICOFLO-510-5053-500-Micron-LDPE-Powder.php

Physical Properties	Metric	English	Comments
Density	0.924 g/cc	0.0334 lb/in ³	ASTM D1505
Particle Size	>= 150 Åµm	>= 150 Åµm	pan, 13%
	<= 500 Åµm	<= 500 Åµm	sieve < 5%
Melt Index of Compound	6.0 g/10 min @Load 2.16 kg, Temperature 190 Å°C	6.0 g/10 min @Load 4.76 lb, Temperature 374 Å°F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	50	50	ASTM D2240
Elongation at Break	100 %	100 %	50 mm/min; ASTM D638
Tensile Modulus	0.200 GPa	29.0 ksi	1 mm/min; ASTM D638

Thermal Properties	Metric	English	Comments
Melting Point	111 Å°C	232 Å°F	DSC; ASTM D3418
Vicat Softening Point	82.0 Å°C	180 Å°F	ASTM D1525

Processing Properties	Metric	English	Comments
Processing Temperature	200 Å°C	392 Å°F	recommended

Descriptive Properties	Value	Comments
Max Dry Flow	max 31 sec/100g	ASTM

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China