

Imerys Alumex,ç Kaolin

Category : Ceramic , Clay , Kaolin Clay

Material Notes:

Alumex is a Hydrated Aluminum Silicate used as a low surface area “soft” filler for Elastomeric systems. Information provided by Imerys

Order this product through the following link:

http://www.lookpolymers.com/polymer_Imerys-Alumex-Kaolin.php

Physical Properties	Metric	English	Comments
Specific Gravity	2.60 g/cc	2.60 g/cc	
Brightness	70 - 80 %	70 - 80 %	% Reflectance
Oil Absorption	26 - 31 %	26 - 31 %	g/100g clay
Particle Size	1.1 Åµm	1.1 Åµm	
Particle Mesh Size	325 Mesh	325 Mesh	0.75% retained
pH	4.0 - 5.0	4.0 - 5.0	
Specific Surface Area	12 - 15 mÅ²/g	12 - 15 mÅ²/g	

Descriptive Properties	Value	Comments
Color	white	
Heating Loss (% max as produced)	1	at 105Å°C

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China