

Imerys ImerPlast[®] 15 Recycled Polyolefin for Pipe Extrusion

Category : Polymer , Renewable/Recycled Polymer , Thermoplastic , Polyolefin

Material Notes:

Polyolefin/Mineral Compound Information provided by Imerys.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Imerys-ImerPlast-15-Recycled-Polyolefin-for-Pipe-Extrusion.php

Physical Properties	Metric	English	Comments
Density	1.04 g/cc	0.0376 lb/in ³	
Melt Flow	0.50 g/10 min	0.50 g/10 min	
	@Load 2.16 kg, Temperature 190 °C	@Load 4.76 lb, Temperature 374 °F	

Mechanical Properties	Metric	English	Comments
Tensile Strength	22.0 MPa	3190 psi	
Flexural Modulus	0.900 GPa	131 ksi	

Processing Properties	Metric	English	Comments
Moisture Content	0.05 %	0.05 %	as packed

Descriptive Properties	Value	Comments
Color	Dark Gray	
Melt Filtration	240 µm	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China