

Imerys ImerPlastâ„¸ 20 Recycled Polyolefin for Pipe Extrusion

Category : Polymer , Renewable/Recycled Polymer , Thermoplastic , Polyolefin

Material Notes:

High Stiffness Polyolefin/Mineral CompoundInformation provided by Imerys.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Imerys-ImerPlast-20-Recycled-Polyolefin-for-Pipe-Extrusion.php

Physical Properties	Metric	English	Comments
Density	1.07 g/cc	0.0387 lb/inÂ³	
Melt Flow	0.35 g/10 min	0.35 g/10 min	
	@Load 2.16 kg, Temperature 190 Â°C	@Load 4.76 lb, Temperature 374 Â°F	

Mechanical Properties	Metric	English	Comments
Tensile Strength	23.0 MPa	3340 psi	
Flexural Modulus	1.00 GPa	145 ksi	

Processing Properties	Metric	English	Comments
Moisture Content	0.05 %	0.05 %	as packed

Descriptive Properties	Value	Comments
Color	Dark Gray	
Melt Filtration	240 Âµm	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China