

Ineos ABS Lustran® SAN DN77 SAN Grade

Category : Polymer , Thermoplastic , SAN Polymer , Styrene Acrylonitrile (SAN), Molded

Material Notes:

Lustran® SAN DN77 is a natural color, styrene-acrylonitrile copolymer supplied in pellet form. It is designed for use in compounding.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ineos-ABS-Lustran-SAN-DN77-SAN-Grade.php

Physical Properties	Metric	English	Comments
Melt Flow	14 g/10 min	14 g/10 min	ASTM-D1238
	@Load 3.80 kg, Temperature 230 Â°C	@Load 8.38 lb, Temperature 446 Â°F	

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	68.9 MPa	10000 psi	ASTM-D638
Flexural Strength	75.8 MPa	11000 psi	at Fail; ASTM-D790
Flexural Modulus	3.45 GPa	500 ksi	ASTM-D790
Izod Impact, Unnotched	3.20 J/cm	6.00 ft-lb/in	ASTM-D256

Thermal Properties	Metric	English	Comments
Vicat Softening Point	109 Â°C	228 Â°F	120Â°C/hour; ASTM-D1525
	@Load 1.00 kg	@Load 2.20 lb	

Descriptive Properties	Value	Comments
Acrylonitrile Content (%)	32.5	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China