

Intercontinental Polymers 131 PET Polymer Type - Semi-Dull, Flame Retardant, Polyester Pellets

Category : Polymer , Thermoplastic , Polyester, TP , Polyethylene Terephthalate (PET) , Polyethylene Terephthalate (PET), Unreinforced

Material Notes:

Applications: Filament Specialties Information provided by Intercontinental Polymers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Intercontinental-Polymers-131-PET-Polymer-Type-Semi-Dull-Flame-Retardant-Polyester-Pellets.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	0.635 - 0.664	0.635 - 0.664	Intrinsic; LCL-PR21

Optical Properties	Metric	English	Comments
Gardner Color Number	2.0 - 5.0	2.0 - 5.0	+ b; LCL-PR01
	61 - 71	61 - 71	Rd; LCL-PR01

Processing Properties	Metric	English	Comments
Melt Temperature	251 Â°C	484 Â°F	LCL-PR29
Moisture Content	<= 0.40 %	<= 0.40 %	LCL-PR08

Descriptive Properties	Value	Comments
COOH	Max 45 meq/kg	LCL-PR09
DEG	0.7 - 1 wt%	LCL-PR11
Phosphorous	2900 - 3300 ppm	
TiO2	0.33 - 0.37 wt%	LCL-PR02

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China