

Iran Petrochemical (PCC) Arak BL3 HDPE

Category : Polymer , Thermoplastic , Polyethylene (PE) , HDPE , High Density Polyethylene (HDPE), Injection Molded

Material Notes:

Information provided by Iran Petrochemical Commercial Co.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Iran-Petrochemical-PCC-Arak-BL3-HDPE.php

Physical Properties	Metric	English	Comments
Density	0.952 - 0.956 g/cc	0.0344 - 0.0345 lb/in ³	DIN 53479
Melt Flow	0.70 - 1.3 g/10 min @Load 5.00 kg, Temperature 190 Â°C	0.70 - 1.3 g/10 min @Load 11.0 lb, Temperature 374 Â°F	DIN 53735
Collected Volatile Condensable Material	<= 0.30 %	<= 0.30 %	BP 138

Mechanical Properties	Metric	English	Comments
Impact	>= 6.5	>= 6.5	mJ/mm2; DIN 53453

Optical Properties	Metric	English	Comments
Yellow Index	<= 4.0 %	<= 4.0 %	DIN 6167

Descriptive Properties	Value	Comments
Contamination	<2 defects in 200 gr of pellets	40-003 HOECHST
Gels	<3	40-042 HOECHST
Melt Fracture	<2	
Swell Ratio	130-160%	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China