

Iran Petrochemical (PCC) PVC-S6558 Poly Vinyl Chloride

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade

Material Notes:

Grade S6558 has low porosity & high bulk density. Applications: pipe and fitting, injection molding
Information provided by Iran Petrochemical Commercial Co.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Iran-Petrochemical-PCC-PVC-S6558-Poly-Vinyl-Chloride.php

Physical Properties	Metric	English	Comments
Bulk Density	0.600 g/cc	0.0217 lb/in ³	DIN-53466
Volatiles	<= 0.20 %	<= 0.20 %	weight %; ISO R-1269
Viscosity Test	105 cm ³ /g	105 cm ³ /g	DIN-53726
Ash	<= 0.050 %	<= 0.050 %	Sulfate ash, weight %; DIN-53568/2

Component Elements Properties	Metric	English	Comments
Chlorine, Cl	56 %	56 %	by weight

Descriptive Properties	Value	Comments
Dark Resin, particles	30	per 250 g PVC; HULS-6.9
K-Value	65	DIN-53726
Residual Vinyl Chloride Monomer, ppm	=1	HULS-6.11

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China