

Kazanorgsintez E-13 Petroleum Resin

Category : Other Engineering Material , Additive/Filler for Polymer

Material Notes:

Production Method: Obtained as a by-product in the process of hydrocarbon gas pyrolysis on ethylene production plants. Application:

Feedstock for production of motor fuel, solvents and aromatic hydrocarbons. Information Provided by Kazanorgsintez

Order this product through the following link:

http://www.lookpolymers.com/polymer_Kazanorgsintez-E-13-Petroleum-Resin.php

Physical Properties	Metric	English	Comments
Density	>= 0.800 g/cc	>= 0.0289 lb/in³	
	@Temperature 20.0 °C	@Temperature 68.0 °F	

Thermal Properties	Metric	English	Comments	
Boiling Point	>= 35.0 °C	>= 95.0 °F	Initial	
	<= 215 °C	<= 419 °F	End	

Component Elements Properties	Metric	English	Comments	
Free Water	<= 1.0 %	<= 1.0 %		

Descriptive Properties	Value	Comments
Appearance	Liquid of light-yellow to brown color, free of mechanical impurities	
Mass Content (%)	45	Mass content of aromatic hydrocarbons (C6- C8)
	8	Mass content of benzene

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China