

LG Chemical DOP Plasticizer

Category : Other Engineering Material , Additive/Filler for Polymer

Material Notes:

Applications: Leather, Sheet, Cable, Gloves, Hoses, Footwear, Wallpaper Information provided by LG Chemical

Order this product through the following link:

http://www.lookpolymers.com/polymer_LG-Chemical-DOP-Plasticizer.php

Physical Properties	Metric	English	Comments
Viscosity	54 cP	54 cP	
Molecular Weight	391 g/mol	391 g/mol	

Thermal Properties	Metric	English	Comments
Melting Point	-55.0 Â°C	-67.0 Â°F	Freezing Point
Boiling Point	386 Â°C	727 Â°F	
Flash Point	206 Â°C	403 Â°F	

Chemical Properties	Metric	English	Comments
Acid Value	<= 0.070 @Treatment Temp. 125 Â°C, Time 10800 sec	<= 0.070 @Treatment Temp. 257 Â°F, Time 3.00 hour	After Heating, KOH mg/g; JIS K6751

Descriptive Properties	Value	Comments
Acidity	<0.02 KOH mg/g	JIS K6751
Color	<20 APHA	JIS K6751
Ester Value	285-289	JIS K6751
Heat Loss	<0.07%	125Â°Cx3hr, JIS K6751

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China