

LG Chemical LUTENE-H ME2500 HDPE

Category : Polymer , Thermoplastic , Polyethylene (PE) , HDPE

Material Notes:

Description: LUTENE-H ME2500 is mainly intended for injection molding of bottle caps. It has good gas permeability characteristics and high toughness. Applications: Caps for beverage bottles CAS No. 9002-88-4 Information provided by LG Chemical

Order this product through the following link:

http://www.lookpolymers.com/polymer_LG-Chemical-LUTENE-H-ME2500-HDPE.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.950 g/cc	0.950 g/cc	ASTM D792
Melt Flow	2.0 g/10 min @Load 2.16 kg, Temperature 190 Â°C	2.0 g/10 min @Load 4.76 lb, Temperature 374 Â°F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	64	64	ASTM D2240
Tensile Strength, Yield	27.5 MPa	3980 psi	ASTM D638
Elongation at Break	>= 1000 %	>= 1000 %	ASTM D638
Flexural Modulus	0.785 GPa	114 ksi	ASTM D790
Izod Impact, Notched	0.981 J/cm @Temperature 23.0 Â°C	1.84 ft-lb/in @Temperature 73.4 Â°F	ASTM D256

Thermal Properties	Metric	English	Comments
Vicat Softening Point	123 Â°C	253 Â°F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China