

Loctite® 334 Acrylic Bonding Adhesive

Category : Polymer , Adhesive , Thermoset , Acrylic/Cyanoacrylate Adhesive

Material Notes:

Acrylic Bonding Adhesives Loctite® Acrylic Adhesives were developed for bonding applications that require tensile, shear and peel strength combined with maximum impact, stress and shock resistance. On contact with an activator, these no-mix materials cure rapidly at room temperature to a weather-resistant bond. Loctite® 334 Acrylic Bonding Adhesive Cure Type: 382 Bonding Type: Acrylic Typical Use: Tough magnet bonder

Order this product through the following link:

http://www.lookpolymers.com/polymer_Loctite-334-Acrylic-Bonding-Adhesive.php

Physical Properties	Metric	English	Comments
Density	1.05 g/cc	0.0379 lb/in ³	
Viscosity	80000 - 140000 cP	80000 - 140000 cP	at 20 RPM; Thixotropic

Mechanical Properties	Metric	English	Comments
Adhesive Bond Strength	19.3 MPa	2800 psi	Varies with substrates

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	149 °C	300 °F	
Minimum Service Temperature, Air	-53.9 °C	-65.0 °F	

Processing Properties	Metric	English	Comments
Cure Time	1.50 min	0.0250 hour	
	1440 min	24.0 hour	Full Cure

Descriptive Properties	Value	Comments
Color	Pale yellow	
Gap Fill	0.02 in.	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China