

Loctite® Gasket Eliminator® 515 Flange Sealant

Category : Polymer , Adhesive , Thermoset

Material Notes:

Anaerobic Gasketing Loctite® 515 Flexible Cure Gasket Eliminator® Flange Sealant Makes flexible gaskets for rigid machined flanges with less than 0.050" gap. Flexes with flanges that move in service. Recommended Primer: 7649 (N). UL classified Typical Use: For flexible applications

Order this product through the following link:

http://www.lookpolymers.com/polymer_Loctite-Gasket-Eliminator-515-Flange-Sealant.php

Physical Properties	Metric	English	Comments
Density	1.10 g/cc	0.0397 lb/in³	
Viscosity	275000 - 950000 cP	275000 - 950000 cP	Thixotropic

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	149 °C	300 °F	
Minimum Service Temperature, Air	-53.9 °C	-65.0 °F	

Processing Properties	Metric	English	Comments
Cure Time	15.0 - 120 min	0.250 - 2.00 hour	Full Cure; Primed
	60.0 - 720 min	1.00 - 12.0 hour	Full Cure; Unprimed

Descriptive Properties	Value	Comments
Color	Purple	
Gap Fill	0.010 in.	Unprimed
	0.05 in.	Primed

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China