

Lubriplate 1444 Aluminum Complex Multi-Purpose Grease

Category: Fluid, Lubricant, Aluminum Gellant

Material Notes:

Tacky aluminum complex grease specifically formulated for heavy-duty construction and mining equipment. Excellent for slow to moderate speed bearings and chains that are subjected to heat, steam, and water. Applications: Heavy-duty construction, mining equip. 1444 is available in Cartridges, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-1444-Aluminum-Complex-Multi-Purpose-Grease.php

Physical Properties	Metric	English	Comments
Saybolt Viscosity at 100°F	3300 SUS	3300 SUS	
Kinematic Viscosity at 40°C (104°F)	626 cSt	626 cSt	

Mechanical Properties	Metric	English Comments	
Penetration P(0), 1/10 mm	265	265	Unknown Amount of Work
Penetration P(60), 1/10 mm	295	295	Unknown Amount of Work

Thermal Properties	Metric	English	Comments
Minimum Service Temperature, Air	-12.2 °C	10.0 °F	Approx. Cold test
Dropping Point	260 °C	500 °F	ASTM Test

Descriptive Properties	Value	Comments
Antiwear (AW)/ Extreme Pressure (EP)	AW/EP	
NLGI Grade	2	
Rust/Oxidative Additives	YES	
Water Resistant	YES	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China