

## **Lubriplate 730-1 Aluminum Complex Multi-Purpose Grease**

Category: Fluid, Lubricant, Aluminum Gellant

## **Material Notes:**

High performance aluminum complex greases that provide high load carrying ability and AW protection with high resistance to water, steam, and other corrosive action. Available in 3 NLGI densities for a wide range of applications and temperatures. No. 730-2 is NLGI GC-LB certified. Applications: Industrial/const. equip. adverse conditions. 730 Series Greases are available in Cans, Pails, 1/4 Drums & Drums.Information provided by Lubriplate

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Lubriplate-730-1-Aluminum-Complex-Multi-Purpose-Grease.php

Physical Properties	Metric	English	Comments
Saybolt Viscosity at 100°F	800 SUS	800 SUS	
Kinematic Viscosity at 40°C (104°F)	151 cSt	151 cSt	

Mechanical Properties	Metric	English	Comments
Penetration P(0), 1/10 mm	310	310	Unknown Amount of Work
Penetration P(60), 1/10 mm	340	340	Unknown Amount of Work

Thermal Properties	Metric	English	Comments	
Minimum Service Temperature, Air	-23.3 °C	-10.0 °F	Approx. Cold test	
Dropping Point	282 °C	540 °F	ASTM Test	

Descriptive Properties	Value	Comments
Antiwear (AW)/ Extreme Pressure (EP)	AW/EP	
NLGI Grade	1	
Rust/Oxidative Additives	YES	
Water Resistant	YES	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel : +86 021-51131842 Mobile : +86 13061808058

Skype: lookpolymers



Address: United North Road 215, Fengxian District, Shanghai City, China