

Lubriplate FMO 1100 AW USP Mineral Oil-Based Food Machinery Grade Oil

Category: Fluid, Lubricant, White Mineral Oil (WMO)

Material Notes:

For use where a Class H-1 oil is required. Manufactured in nine ISO grades for a variety of applications. Anti-wear fortified. NOTE: FMO-350AW is also available in a red and orange color which helps in leak detection. FMO-1100AW and FMO-2400AW pass 12 stages of the FZG test. The original FMO Series products without the anti wear additive system are still available. FMO Series Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums.H-1 Class Lubricants are manufactured with ingredients that comply with FDA regulation 21 CFR 178.3570 for lubricants with incidental contact with the edible product. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-FMO-1100-AW-USP-Mineral-Oil-Based-Food-Machinery-Grade-Oil.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	100	100	Viscosity Index
	220	220	ISO Grade
Saybolt Viscosity at 100°F	1126 SUS	1126 SUS	
Saybolt Viscosity at 210°F	97 SUS	97 SUS	
Kinematic Viscosity at 40°C (104°F)	210 cSt	210 cSt	
Kinematic Viscosity at 100°C (212°F)	19 cSt	19 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-15.0 °C	5.00 °F	
Flammability Test	510	510	[°F] Fire Point
Flash Point	227 °C	440 °F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	90	
SAE No.	50	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058



Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China