

Lubriplate MV-HO Petroleum-Based Heavy-Duty Hydraulic Oil

Category : Fluid , Lubricant

Material Notes:

ISO 32 petroleum-based oil for low temperature applications. Low Temp Hydraulic Oils are available in Jugs, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-MV-HO-Petroleum-Based-Heavy-Duty-Hydraulic-Oil.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	32	32	ISO Grade
	199	199	Viscosity Index
Saybolt Viscosity at 100°F	186 SUS	186 SUS	
Saybolt Viscosity at 210°F	53 SUS	53 SUS	
Kinematic Viscosity at 40°C (104°F)	35 cSt	35 cSt	
Kinematic Viscosity at 100°C (212°F)	8.0 cSt	8.0 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-45.6 °C	-50.0 °F	
Flammability Test	380	380	[°F] Fire Point
Flash Point	177 °C	350 °F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	75	
SAE No.	5W-20	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China