

Lubriplate SYNCOOL 32 Polyglycolester-Based Synthetic Air Compressor Fluid

Category : Fluid , Lubricant , Polyglycol

Material Notes:

These polyglycolester-based synthetic fluids are designed for rotary screw air compressors. They offer excellent heat transfer properties, low evaporation, high flash points, and outstanding oxidation resistance, eliminating varnish and sludge. Fluid change intervals are 8,000 hours under normal operating conditions. Syncool Series Fluids are available in Pails & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-SYNCOOL-32-Polyglycolester-Based-Synthetic-Air-Compressor-Fluid.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	32	32	ISO Grade
	156	156	Viscosity Index
Saybolt Viscosity at 100°F	165 SUS	165 SUS	
Saybolt Viscosity at 210°F	34 SUS	34 SUS	
Kinematic Viscosity at 40°C (104°F)	30 cSt	30 cSt	
Kinematic Viscosity at 100°C (212°F)	6.0 cSt	6.0 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-51.1 °C	-60.0 °F	
Flammability Test	550	550	[°F] Fire Point
Flash Point	252 °C	485 °F	

Descriptive Properties	Value	Comments
SAE No.	10	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China