

Lubrizol Advanced Materials Pearlstick® 49-46/19 Polyester based TPU (discontinued **)

Category : Polymer , Thermoplastic , Polyurethane, TP , Thermoplastic Polyurethane (TPUR), Polyester Grade

Material Notes:

TPUs for Solvent-based adhesivesApplications: ShoelInformation provided by Merquinsa

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubrizol-Advanced-Materials-Pearlstick-49-4619-Polyester-based-TPU-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Viscosity	1700 - 2100 cP	1700 - 2100 cP	15% solution in MEK

Processing Properties	Metric	English	Comments
Processing Temperature	65.0 °C	149 °F	Min. Activation Temp; EN 12961

Descriptive Properties	Value	Comments
Crystallization Rate (MQSA n° 12 A)	VERY HIGH	
Solubility - Acetone / Ethyl Acetate	75:25	
Solubility - Acetone / Toluene	70:30	
Solubility - MEK / Toluene	80:20	
Solubility - MEK/ Ethyl Acetate	80:20	
Thermoplasticity Range (MQSA n° 58)	LOW	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China