

Lucite International Colacryl ® LS200 Specialty Acrylic Resin

Category: Polymer, Thermoplastic, Acrylic (PMMA)

Material Notes:

Colacryl® LS200 is a medium-high molecular weight methyl methacrylate polymer. It is used mainly in coating applications where abrasion resistance and resistance to plasticiser migration are important. Applications: Coatings on supported and unsupported plasticised PVC; Abrasion resistant coatings on plastics (e.g. Polystyrene)Information provided by Lucite International

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lucite-International-Colacryl-LS200-Specialty-Acrylic-Resin.php

Physical Properties	Metric	English	Comments
Density	1.16 g/cc	0.0419 lb/in³	
Viscosity	>= 10000 cP	>= 10000 cP	

Thermal Properties	Metric	English	Comments
Glass Transition Temp, Tg	105 °C	221 °F	

Chemical Properties	Metric	English	Comments
Total Acid Number	0.00	0.00	

Processing Properties	Metric	English	Comments
Moisture Content	0.80 %	0.80 %	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China