

Lucite International Elvacite Â® 4104 Acrylic Resin

Category : Polymer , Thermoplastic , Acrylic (PMMA)

Material Notes:

ElvaciteÂ® 4104 is designed for use in self-levelling flooring formulations, but can be used in a variety of coatings formulations, such as covercoats, heat seal lacquers and plastic coatings. It has excellent flexibility and good gloss. Additionally, it is compatible with a wide range of binders and waxes. Solutions of ElvaciteÂ® 4104 in methyl methacrylate monomer show unusually good viscosity stability, making this product an extremely good choice for Monomer/Polymer (MoPo) systems. Information provided by Lucite International

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lucite-International-Elvacite-4104-Acrylic-Resin.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	0.52 - 0.60	0.52 - 0.60	reduced viscosity (dl/g), 1 wt% in chloroform; Ubbelohde B Viscometer
Molecular Weight	135000 g/mol	135000 g/mol	

Thermal Properties	Metric	English	Comments
Glass Transition Temp, Tg	40.0 Â°C	104 Â°F	

Chemical Properties	Metric	English	Comments
Total Acid Number	0.00	0.00	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China