

M. Holland Company CP910 Polypropylene Impact Copolymer

Category : Polymer , Thermoplastic , Polypropylene (PP)

Material Notes:

Antistatic Impact copolymer High flow Nucleated Slip High stiffness Applications: Containers Household goods Thin-walled parts

Order this product through the following link:

http://www.lookpolymers.com/polymer_M-Holland-Company-CP910-Polypropylene-Impact-Copolymer.php

Physical Properties	Metric	English	Comments
Density	0.900 g/cc	0.0325 lb/in ³	ASTM D1505
Melt Flow	100 g/10 min	100 g/10 min	ASTM D1238
	@Load 2.16 kg, Temperature 230 Â°C	@Load 4.76 lb, Temperature 446 Â°F	

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	27.6 MPa	4000 psi	ASTM D638
Elongation at Yield	5.0 %	5.0 %	ASTM D638
Flexural Modulus	1.38 GPa	200 ksi	ASTM D790
Izod Impact, Notched	0.427 J/cm	0.800 ft-lb/in	73Â°F; ASTM D256

Descriptive Properties	Value	Comments
Characteristics	Antistatic, Nucleating agent, Slip	
Forms	Pellets	
Processing Methods	Injection molding	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China