

Michelman® Michem® Guard 55 Nonionic polyethylene dispersion

Category: Fluid, Other Engineering Material, Additive/Filler for Polymer, Polymer, Thermoplastic, Polyethylene (PE)

Material Notes:

Description: Nonionic polyethylene dispersionUsage: Michem® Guard 55 is a dispersion which provides mar and flatting properties when used as an additive in paint, coating, ink and graphic art formulations. Typical uses include: Inks and OPVs; Exterior wood and wood composites and Interior furniture and flooringFood Contact Information when manufactured in Belgium:FDA:175.105: Components of adhesives. 176.170: Components of paper and paperboard in contact with aqueous and fatty foods. (Restricted) 176.180: Components of paper and paperboard in contact with dry foods. Information provided by Michelman®

Order this product through the following link:

http://www.lookpolymers.com/polymer_Michelman-Michem-Guard-55-Nonionic-polyethylene-dispersion.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.970 - 0.990 g/cc	0.970 - 0.990 g/cc	
Volatiles	59.5 - 60.5 %	59.5 - 60.5 %	
pH	2.0 - 12	2.0 - 12	Recommended pH of system
	6.5 - 8.5	6.5 - 8.5	
Brookfield Viscosity	500 - 5000 cP	500 - 5000 cP	Spindle # 4, rpm 60

Descriptive Properties	Value	Comments		
Appearance	White, free-flowing paste	White, free-flowing paste		
Emulsifier Charge	Nonionic	Nonionic		
Solids Type	Polyethylene			

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China